

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A computer readable medium containing a database structure for storage of encrypted data, the database structure comprising:

at least one data entity encrypted by at least one encryption key, the data entity having at least one searchable attribute; ~~and~~
at least one encryption key identification stored in association with the data entity ~~and~~
corresponding to the encryption key for identifying the encryption key, wherein the encryption key identification is encrypted by a system key; and
a system key common name also stored in association with the data entity for identifying the system key, wherein the system key common name is encrypted by a master key.

Claim 2 (canceled).

Claim 3 (currently amended): The computer readable medium according to claim 2 1 wherein the system key common name is hashed, and the database structure further comprises the system key common name hash value stored in association with the system key common name.

Claim 4 (original): The computer readable medium according to claim 3 wherein the system key common name and the system key common name hash value are stored on a separate database from the at least one data entity.

Claim 5 (canceled).

Claim 6 (original): The computer readable medium according to claim 1 wherein the at least one encryption key comprises a dynamic encryption key, and the at least one encryption key identification comprises a dynamic encryption key identification.

Claim 7 (original): The computer readable medium according to claim 1 further comprising a plurality of data entities encrypted by a plurality of encryption keys, and a plurality of encryption key identifications.

Claim 8 (original): The computer readable medium according to claim 7 wherein the plurality of encryption keys comprise dynamic encryption keys, and the plurality of encryption key identifications comprise dynamic encryption key identifications.

Claim 9 (original): The computer readable medium according to claim 1 wherein the data structure further comprises a plurality of hash values with each of the searchable attributes having a corresponding hash value.

Claim 10 (original): The computer readable medium according to claim 1 wherein the data structure further comprises at least one integrity attribute in association with the data entity.

Claim 11 (original): The computer readable medium according to claim 1 wherein the data structure further comprises a security key attribute of the data entity, the security key attribute including the at least one encryption key identification and a system key common name.

Claim 12 (original): The computer readable medium according to claim 1 further comprising a first database including the data entity and encryption key identification stored thereon and a second database including the encryption key stored thereon.

Claim 13 (canceled).

Claim 14 (currently amended): The computer readable medium according to claim ~~13~~ 12 further comprising a security token including the system key stored thereon.

Claim 15 (original): The computer readable medium according to claim 14 wherein the security token comprises a Smart Card reader.

Claim 16 (original): The computer readable medium according to claim 1 wherein the at least one encryption key identification is stored as an attribute of the data entity.

Claim 17 (original): The computer readable medium according to claim 1 wherein the data entity comprises a data object having a plurality of attributes.

Claim 18 (original): The computer readable medium according to claim 1 further comprising a second data entity including as attributes the encryption key and the encryption key identification.

Claim 19 (original): The computer readable medium according to claim 18 wherein the second data entity is stored on a separate isolated database from the at least one data entity.

Claim 20 (original): The computer readable medium according to claim 1 further comprising a second data entity encrypted by a second encryption key, the second data entity having a second searchable attribute, and a second encryption key identification corresponding to the second encryption key; and wherein the at least one encryption key comprises a first encryption key and the at least one encryption key identification comprises a first encryption key identification.

Claim 21 (original): The computer readable medium according to claim 20 wherein the second encryption key identification is stored as an attribute of the second data entity.

Claim 22 (original): The computer readable medium according to claim 20 wherein the first and second encryption key identifications are encrypted by a system key having a system key common name.

Claim 23 (original): The computer readable medium according to claim 22 wherein the system key comprises a public system key.

Claim 24 (original): The computer readable medium according to claim 22 further comprising the system key common name stored as an attribute of the first and second data entities.

Claim 25 (original): The computer readable medium according to claim 20 wherein the first encryption key identification is encrypted by a first system key, and the second encryption key identification is encrypted by a second system key.

Claim 26 (original): The computer readable medium according to claim 20 wherein the first and second data entities contain information for an individual customer.

Claim 27 (original): The computer readable medium according to claim 26 wherein the first data entity contains medical patient name information, and the second data entity contains medical patient address information.

Claim 28 (currently amended): A computer readable data transmission medium containing a data structure for encrypted data, the data structure comprising:

at least one data entity encrypted by at least one encryption key, the data entity having at least one searchable attribute; ~~and~~
at least one encryption key identification stored in association with the data entity ~~and~~
corresponding to the encryption key for identifying the encryption key, wherein the encryption key identification is encrypted by a system key; and
a system key common name also stored in association with the data entity for identifying the system key, wherein the system key common name is encrypted by a master key.

Claims 29-39 (canceled).

Claim 40 (currently amended): A method for storage and retrieval of encrypted data, the method comprising:

encrypting a data entity with an encryption key having an encryption key identification;
storing the encrypted data entity; ~~and~~
encrypting the encryption key identification with a system key having a system key common name;
encrypting the system key common name with a master key; and
storing the encrypted encryption key identification and the encrypted system key common name in association with the encrypted data entity.

Claim 41 (currently amended): The method according to claim 40 further comprising:
requesting a data manipulation using a searchable attribute;
searching for matches to the searchable attribute;
decrypting the system key common name using the master key;
searching for the system key using the system key common name;
decrypting the encryption key identification with the system key;
searching for the encryption key using the encryption key identification; and
decrypting the data entity with the encryption key.

Claim 42 (original): The method according to claim 41 wherein requesting the data manipulation comprises requesting a data update of new information, and further comprising encrypting the new information with a second encryption key.

Claim 43 (original): The method according to claim 41 wherein requesting the data manipulation comprises requesting an addition of new information, and further comprising encrypting the new information with a second encryption key.

Claim 44 (original): The method according to claim 41 wherein requesting the data manipulation comprises requesting viewing of current information, and further comprising encrypting the viewed information with a second encryption key

Claim 45 (canceled).

Claim 46 (currently amended): The method according to claim ~~45~~ 40 further comprising storing the system key in a security token.

Claim 47 (canceled).

Claim 48 (currently amended): The method according to claim ~~45~~ 40 wherein encrypting the encryption key identification with a system key comprises encrypting the encryption key identification with a system public key.

Claim 49 (original): The method according to claim 48 further comprising decrypting the encryption key identification with a system private key.

Claim 50 (canceled).

Claim 51 (currently amended): The method according to claim ~~45~~ 40 further comprising checking for expiration of the system key, and upon expiration of the system key, discontinuing use of the system key and generating and using a new system key.

Claim 52 (original): The method according to claim 51 further comprising upon expiration of the system key, retaining the system key for decrypting previously encrypted encryption key identifications.

Claim 53 (currently amended): The method according to claim 40 further comprising ~~encrypting the encryption key identification with a system key having a system key common name,~~ hashing the system key common name to create a system key common name hash value, encrypting the system key common name hash value with the master key, and storing the encrypted system key common name and the encrypted system key common name hash value in association with the data entity.

Claim 54 (previously presented): The method according to claim 53 further comprising:
requesting a data manipulation using a searchable attribute;
searching for matches to the searchable attribute;
searching for the system key common name using the system key common name hash value;
searching for the system key using the system key common name;
decrypting the encryption key identification with the system key;
searching for the encryption key using the encryption key identification; and decrypting the data entity with the encryption key.

Claim 55 (original): The method according to claim 53 further comprising verifying the system key with a private certificate authority, and performing an integrity check on the system key.

Claim 56 (original): The method according to claim 40 further comprising checking the encryption key for expiration.

Claim 57 (original): The method according to claim 56 further comprising upon expiration of the encryption key, generating a new encryption key having an expiration date, retrieving data entities using the encryption key, decrypting the retrieved data entities with the encryption key, encrypting the retrieved data entities with the new encryption key, storing the retrieved data entities.

Claim 58 (previously presented): The method according to claim 40 further comprising hashing searchable attributes of the data entity to determine data entity attribute hash values and storing the data entity attribute hash values in association with the data entity.

Claim 59 (currently amended): The method according to claim 58 further comprising:
requesting a data manipulation using a searchable attribute;
hashing the searchable attribute to create a searchable attribute hash value;
searching for matches to the searchable attribute hash value;
decrypting the system key common name using the master key;
searching for the system key using the system key common name;
decrypting the encryption key identification with the system key;
searching for the encryption key using the encryption key identification; and
after retrieving the encryption key, decrypting the data entity with the encryption key.

Claim 60 (original): The method according to claim 40 further comprising transmitting the data entity over a data transmission line, and wherein encrypting the data entity comprises encrypting only a portion of the data entity in accordance with a business rule.

Claim 61 (original): The method according to claim 40 further comprising generating a new encryption key for each user session.

Claim 62 (original): The method according to claim 40 further comprising generating a new encryption key for each user action.

Claim 63 (original): The method according to claim 40 further comprising retrieving the encryption key from a separate database, and decrypting the data entity with the encryption key.

Claim 64 (original): The method according to claim 40 further comprising auditing the encryption key for a desired event.

Claim 65 (original): The method according to claim 40 wherein the data entity and encryption key identification are stored in a first database, and further comprising storing the encryption key in a second database.

Claim 66 (original): The method according to claim 40 further comprising encrypting the encryption key identification with a system key having a system key common name, and maintaining the system key within a security domain at all times.

Claim 67 (currently amended): The method according to claim 40 further comprising:
requesting a data manipulation using a searchable attribute;
searching for matches to the searchable attribute;
decrypting the system key common name using the master key;
searching for the system key using the system key common name;
decrypting the encryption key identification with the system key;
searching for the encryption key using the encryption key identification;
performing an integrity check on the encryption key; and
decrypting the data entity with the encryption key.

Claim 68 (original): A method for retrieval of encrypted data at rest, the method comprising:

requesting a data manipulation using a searchable attribute;
searching a plurality of data entities for matches to the searchable attribute;
obtaining an encryption key identification from the data entities;
searching for an encryption key using the encryption key identification; and
decrypting the data entities with the encryption key.

Claim 69 (previously presented): The method according to claim 68 further comprising:
obtaining a system key common name from the data entities;
searching for a system key using the system key common name;
decrypting the encryption key identification with the system key.

Claim 70 (currently amended): A method for storage and retrieval of encrypted data, the method comprising:

encrypting a plurality of data entities with a rotating and dynamic encryption key having an encryption key identification;

storing the encrypted data entities; and

encrypting the encryption key identification with a system key having a system key identification;

encrypting the system key identification with a master key; and

storing the encrypted encryption key identification and the encrypted system key identification with the encrypted data entity; and

creating and rotating to a new encryption key upon occurrence of a desired rotation event.

Claim 71-97 (canceled).

Claim 98 (currently amended): A method of providing a secure environment for the storage of information, the method comprising:

encrypting a data entity with an encryption key having a randomly generated encryption key identification;

storing the encrypted data entity; ~~and~~

encrypting the encryption key identification with a system key having a system key identification;

encrypting the system key identification with a master key; and

storing the encrypted encryption key identification and the encrypted system key identification in association with the encrypted data entity.

Claims 99-120 (canceled).

Claim 121 (new): A method of encrypting and storing a data entity, the method comprising the steps of:

- encrypting a data entity using a first encryption key having a first encryption key identification;
- encrypting the first encryption key identification using a second encryption key having a second encryption key identification;
- encrypting the second encryption key identification using a third encryption key;
- storing the encrypted data entity, the encrypted first encryption key identification, and the encrypted second encryption key identification together;
- encrypting the first encryption key using a fourth encryption key having a fourth encryption key identification;
- encrypting the fourth encryption key identification using the third encryption key;
- encrypting the second and fourth encryption keys using the third encryption key;
- storing the unencrypted first encryption key identification, the encrypted fourth encryption key identification, and the encrypted first encryption key together;
- storing the unencrypted second encryption key identification and the encrypted second encryption key together;
- storing the unencrypted fourth encryption key identification and the encrypted fourth encryption key together; and
- securing the third encryption key.

Claim 122 (new): The method as set forth in claim 121, wherein the second encryption key identification is a system key common name.

Claim 123 (new): The method as set forth in claim 121, wherein the second encryption key identification is a system key common name hash value.

Claim 124 (new): A method of encrypting, storing, and decrypting a data entity, the method comprising the steps of:

encrypting and storing the data entity as follows -

encrypting a data entity using a first encryption key having a first encryption key identification,

encrypting the first encryption key identification using a second encryption key having a second encryption key identification,

encrypting the second encryption key identification using a third encryption key, storing the encrypted data entity, the encrypted first encryption key identification, and the encrypted second encryption key identification together,

encrypting the first encryption key using a fourth encryption key having a fourth encryption key identification,

encrypting the fourth encryption key identification using the third encryption key,

encrypting the second and fourth encryption keys using the third encryption key, storing the unencrypted first encryption key identification, the encrypted fourth encryption key identification, and the encrypted first encryption key together,

storing the unencrypted second encryption key identification and the encrypted second encryption key together,

storing the unencrypted fourth encryption key identification and the encrypted fourth encryption key together,

securing the third encryption key; and

decrypting the data entity as follows -

accessing the third encryption key and using the third encryption key to decrypt the second encryption key identification and the fourth encryption key identification,

identifying the second encryption key using the decrypted second encryption key identification,

using the second encryption key to decrypt the first encryption key identification,

identifying the first encryption key using the decrypted first encryption key
identification,
identifying the fourth encryption key using the decrypted fourth encryption key
identification,
using the fourth key to decrypt the first encryption key, and
using the decrypted first encryption key to decrypt the data entity.

Claim 125 (new): The method as set forth in claim 124, wherein the second encryption
key identification is a system key common name.

Claim 126 (new): The method as set forth in claim 124, wherein the second encryption
key identification is a system key common name hash value.